

Quick Start Guide of Creating .war and .jar for the RFID Enabling Engine


Product Version: Version 1.0

Table of Contents


Table of Contents	2
Setup Ant	3-8
Building war and jar	8-9

Setup Ant:

Step 1: Copy the Build folder to local directory and extract the apache-ant-1.7.1-bin file as follow:




The "apache-ant-1.7.1" folder will be created if success.




Step 2: Configure the system path as follow:


- First, right click (My Computer /我的電腦) and select (Properties/內容):
- Select the (Advanced/進階) tab as follow:




- Click the (Environment variable /環境變數) as follow:




The following window will be popup if success:



- Find the (System variable/ 系統變數) call "PATH" in the bottom as follow:




- Click (Modify / 編輯) and append the location of the “bin” directory which created in Step 1 (.....\apache-ant-1.7.1\bin) in (Variable Value/變數值) as follow:




- Finally, click (OK/確定).

Step 3: Configure the ANT_HOME as follow:

- Click (Add/新增) in the bottom as follow:



- Type "ANT_HOME" in Variable Name/ 變數名稱
- Type the ant directory location which is created in Setup Ant Step 1.




- Finally, click (OK/確定) in both window.

Step 4: Restart computer.

- Close all the application and restart the computer.

Building war and jar:

- Open Window command prompt (Type 'cmd' in Startup->Run /開始->執行)
- Change the directory to the project location where the build.xml and build.properties locate:
(Type 'cd path' in command prompt where path equals the project location where the build.xml and build.properties locate)



- Type 'ant' in the command prompt and the following message will be shown if success.

```

C:\WINDOWS\system32\cmd.exe
eREWeb\dist\WEB-INF\classes

compile:
  [javac] Compiling 54 source files to C:\Documents and Settings\k\桌面\osree\
  OpenSourceREWeb\dist\WEB-INF\classes
  [javac] Note: Some input files use or override a deprecated API.
  [javac] Note: Recompile with -Xlint:deprecation for details.
  [javac] Note: Some input files use unchecked or unsafe operations.
  [javac] Note: Recompile with -Xlint:unchecked for details.

package:
  [jar] Building jar: C:\Documents and Settings\k\桌面\osree\jar\osree.jar

deploy:
  [jar] Building jar: C:\Documents and Settings\k\桌面\osree\OpenSourceREWeb
  b\WebRoot\WEB-INF\osree.war
  [copy] Copying 1 file to C:\Documents and Settings\k\桌面\osree\war
  [delete] Deleting: C:\Documents and Settings\k\桌面\osree\OpenSourceREWeb\We
  bRoot\WEB-INF\osree.war
  [delete] Deleting directory C:\Documents and Settings\k\桌面\osree\OpenSource
  REWeb\dist

BUILD SUCCESSFUL
Total time: 15 seconds
C:\Documents and Settings\k\桌面\osree\OpenSourceREWeb\WebRoot\WEB-INF>
    
```

- The created .war and .jar file will be stored in the folder "jar" and "war" respectively with the same level of the project as follow:

